

# **Hakwood** GREAT FLOORING STORIES

## HAKWOOD Care and Maintenance products



Maintenance 1 ltr/ 33.81 fl oz

Flooring Wash 1 ltr/ 33.81 fl oz

Power Cleanser 1 ltr/ 33.81 fl oz

Set of Maintenance, Flooring Wash & Power Cleanser

# Hakwood

GREAT FLOORING STORIES

## Care & Maintenance Instructions Hakwood Oiled and DuoVarnish Floors

### Important!

Newly delivered pre-finished flooring by Hakwood requires three weeks to harden completely. During the first week, we recommend only cleaning with a vacuum cleaner or a dust mop fitted with a dry cloth. Do NOT use a damp cloth!

During the second week, wipe gently with a damp cloth that has been soaked in clean water and wrung out thoroughly.

After the third week, the floor can be maintained using Hakwood's maintenance products per these instructions. On locations with very heavy traffic, the surface should preferably be covered for the first week with a porous protecting material.

### **Weekly Maintenance:**

Hakwood Flooring Wash  
Article number 700.8600

Frequency: Use weekly.

- Sweep the floor and eliminate dust.
- Pour 2 filling caps of Hakwood Flooring Wash into a bucket of water (5 L / 1.32 gal).
- Use 2 buckets: one for the soap and water mixture and the other for clean water only.
- Immerse the mop in the soapy water and wring it out until it is only half wet. Clean the first section of the floor. Rinse the mop in the bucket of clean water and wring it out thoroughly. Immerse the mop in the soapy water and wring it out until it is only half wet. Clean the next section of the floor.
- Do not leave any surplus water on the floor. Damp-mopping is sufficient. Do not walk on the floor until it is completely dry (30 minutes).

Weekly maintenance with Hakwood Flooring Wash maintains the floor's matt finish.

### **Intensive Cleaning:**

Only when necessary – no colour restoration.

Hakwood Power Cleanser  
Article number 700.8620

Frequency: Use when dirty spots appear.

- \_ Eliminate dirt and dust from the floor.
  - \_ Dilute in 1:10 ratio with clean water.
  - \_ Apply evenly and thoroughly on floor surface.
  - \_ Allow the product to react for a couple of minutes.
  - \_ Wipe dry with a cloth, paper towel, or polishing machine with white pad. Finish the treatment using an absorbent cloth until the surface feels completely dry.
  - \_ Pay attention to handle medium sized zones that can be fully wiped dry within 15 to 20 minutes.
- Make sure zones are not done twice. The surface can be walked on after 2 hours.

Consumption: 1 liter = +/- 100m<sup>2</sup>  
(0.26 gal= +/- 1076.4 sq feet).

### **Refreshment:**

Only when necessary – no colour restoration.

Hakwood Maintenance  
Article number 700.8610

Frequency: Use when needed to protect and refresh rough spots.

- \_ Eliminate dirt and dust from the floor.
- \_ Apply small amount of the Hakwood Maintenance, about 1 filling cap per 2 m<sup>2</sup> (21.52 sq ft).

\_ Allow the product to react for a couple of minutes. The product removes dirt stains, watermarks, etc.

\_ Wipe dry with a cloth, paper towel, or polishing machine with white pad.

\_ Pay attention to handle medium sized zones that can be fully wiped dry within 15 to 20 minutes.

\_ Make sure zones are not done twice. The surface can be walked on after 2 hours.

Consumption: 1 liter = +/- 100m<sup>2</sup>

(0.26 gal= +/- 1076.4 sq feet).